

Warranty

The warranty of this product is 1 year from the date of purchase.

The lifetime estimated of this product is 3 year, but the lifetime can be more or less depended on the frequency of using the product and how users follow the instruction manual to avoid any damage to this product.

Every year periodic examination has to be done by an authorized person or by the manufacturer.

Manufacture conformed to EN795 and EN1496 standard

PAT NBK CO., LTD.
No.103, Renmei Rd., Dali Dist, Taichung City 412, Taiwan
www.patnbk.com.tw

EC type examination & design stage is carried out by notified body:

INSPEC International Limited
Notified Body number: 0194
56 Leslie Hough Way Salford Greater Manchester
M6 6AJ United Kingdom

Notified body involved in the production control phase

SGS UNITED KINGDOM LIMITED
202b, Worle Parkway, Weston-Super-Mare, BS22 6WA,
United Kingdom
Phone : +44 (0)1934 522917
Fax : +44 (0)1934 522137
Email : sgsprodcert@sgs.com
Website : www.uk.sgs.com



Tripod and Winch

INSTRUCTION MANUAL
Tripod Conform to EN 795: 2012 Class B,
Winch conform to EN 1496:2006 Class A

Application

For tripod it own, it is suitable used on confined spaces, manholes, tanks, hatches and other below ground work for fall arrest protection. When this tripod use with together the hand winch, it's shall only be used for rescue purposes. This device is for one person use only! The user should read and understand the information in this user information sheet before using this device for fall arrest protection and rescue lifting purpose.

Model:

HD-240-20
HD-240-25
HD-240-30
HD-240-35



Technical Data

Device	Model	maximum rated load	Working Length	Material	Weight
Tripod And Winch	HD-240-20	100KG	20M	Aluminum	33 KG
	HD-240-25	100KG	25M	Aluminum	33 KG
	HD-240-30	100KG	30M	Aluminum	34 KG
	HD-240-35	100KG	35M	Aluminum	34 KG